

SEER 20 DC Inverter technology



Wireless remote control
Easy to understand



- Multi-zone system
- Single, Dual or Tri zones



We think green...

DC Inverter System. High performance in cooling/heating mode
Low noise operation
NEO-PLASMA filter . Intelligent self-control
Four-dimensional swing pattern air delivery technology
Stronger heating capability. Low temperature heating
Eco-friendly refrigerant R410A and more...

Model number		DLDI09SS1A/B	DLDI12SS1A/B	DLDI18SS1A/B	DLDI24SS1A/B
Capacity (BTU)		DC Inverter 9K	DC Inverter 12K	DC Inverter 18K	DC Inverter 24K
Cooling (BTU)		10000	12000	20000	24000
Heating (BTU)		11000	15500	20500	28000
SEER		20.00	20.00	20.00	20.00
HSPF		10	10	10	10.5
EER		14	14	14	14
Voltage		115/60	115/60	230/60	230/60
Current (A) Rated/Max Cooling	Cooling	5.5/9.32	7.53/10.8	5.929/10.1	11.09/12.22
	Heating	7.1/9.8	10.4/13.0	6.732/9.31	10.24/12.23
Power Consumption (KW)Rated/Max Cooling	Heating	0.61/1.06	0.862/1.236	1.345/2.3	2.504/2.765
	Heating	0.8/1.11	1.19/1.496	1.532/2.124	2.314/2.768
Indoor Noise level dB(A): H / M / L		35/30/30	40/35/35	45/40/37	45/40/37
Outdoor Noise Level dB(A)		~ 55	~ 55	~ 55	~ 55
Connection Method		Flare	Flare	Flare	Flare
Pipe Size (In.)		1/4" / 3/8"	1/4" / 1/2"	3/8" / 5/8"	3/8" / 5/8"
Indoor Dimensions W x D x H(In.)		30x12x10	35.5x12x11	42.5x12x12	47x13x12
Indoor Net Weight (lbs.)		22	31	40	44
Indoor Gross Weight (lbs.)		26	37	51	55
Outdoor Dimensions W x D x H(In.)		35.6x12.7x22.6	38.6x15.7x26.0	38.2x15.6x29.9	40.2x17.1x34.1
Refrigerant		R410 A	R410 A	R410 A	R410 A



more than comfort...

